



EXIUM Technologies, Inc.
 263 South Street East
 Raynham, MA 02767
 Phone: (508)-824-0015
 Fax: (508)-824-0101

24 Hour Emergency Telephone – (PERS) In US and Canada Call: 1-800-633-8253
 Internationally Call Collect: 1-801-629-0667

MATERIAL SAFETY DATA SHEET

Issued: 1/9/12

Section 1 – IDENTIFICATION

Product Name: **32126H150**

**DD SIZE LITHIUM /
 THIONYL CHLORIDE CELL
 HIGH RATE ELECTRODES**

Lithium Content: 8.02 grams

<u>Hazardous Components</u>	<u>(Approx. %)</u>
Lithium	3 - 4%
Thionyl Chloride	30 - 35%
Gallium Chloride (GaCl ₃)	5 - 7%
Lithium Chloride	1 - 2%

<u>Non-Hazardous Components</u>	<u>(Approx. %)</u>
Stainless Steel	40 - 46%
Nickel	1 - 5%
Glass Separator	1 - 3 %
Carbon	3 - 4%
Other	3 -6%

Section 2 – HAZARDOUS INGREDIENTS COMPOSITION / INFORMATION

Thionyl Chloride CAS# 7719-09-17	OSHA: None Established ACGIH: 1.0 ppm (5.0 mg/m ³) ceiling
Gallium (III) Chloride CAS # 13450-90-3	OSHA: None Established ACGIH: None Established Exium Recommended based on AlCl ₃ : 2 mg/m ³ TLV/TWA
Lithium CAS # 7439-93-2	OSHA: None Established ACGIH: None Established
Lithium Chloride CAS # 7447-41-8	OSHA: None Established ACGIH: None Established

Section 3 – HAZARDS IDENTIFICATION

Note: The cell or battery described in this MSDS is a hermetically sealed stainless steel unit. There are no contacts or exposures from handling or using this cell or battery under normal conditions. Contact or exposure to the internal components can only occur if the cell or battery has leaked, been crushed, vented, or exploded.

DANGER: INTERNAL CONTENTS ARE EXTREMELY HAZARDOUS. LEAKING FLUID IS CORROSIVE. BATTERY MAY EXPLODE IF EXPOSED TO TEMPERATURES ABOVE 180 °C, EXPOSED TO FIRE, CHARGED, SHORT CIRCUITED, OR CRUSHED.

Do not expose to temperatures above 150°C due to leak hazard.

If cell or battery leaks or vents

Primary Routes of Entry: Inhalation

Carcinogenicity: Not listed by NTP, IARC, or regulated by OSHA.

Health Hazards: **Acute** – Vapors are very irritating to skin, eyes, and mucous membranes. Inhalation of large quantities of thionyl chloride may result in pulmonary edema.

Chronic – Overexposure can cause symptoms of non-fibrotic lung injury

Signs and Symptoms of Exposure: Eye and mucous membrane irritation.

Medical Conditions Generally Aggravated by Exposure: Asthma, other respiratory disorders, skin allergies, and eczema.

Section 4 – FIRST AID MEASURES

Eye Contact: Flush with running water for at least 15 minutes. Hold eyelids apart. Seek immediate medical attention. Contact results in acidic burns.

Skin Contact: Rinse with large amounts of running water. Avoid hot water and rubbing skin. A baking soda paste applied to the contact will assist in neutralizing any acid present. If burns develop, seek medical attention. Contact results in acidic burns from decomposition products HCl and SO₂.

Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. Inhalation of large quantities of thionyl chloride may result in pulmonary edema.

Ingestion: Drink copious amounts of water (or milk if available). Do not induce vomiting. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. Immediately seek medical attention.

Section 5 – FIRE FIGHTING MEASURES

Flash Point: N/A

Auto-Ignition Temp: N/A

Flammable Limits: N/A

Danger - Do not use water

Extinguisher Media: Lith-X powder, Class D fire extinguisher, Dry Lithium Chloride, Graphite Powder, Pyrene G-1.

Special Fire Fighting Procedures: Cover with Lith-X powder, Class D fire extinguisher, dry lithium chloride, or graphite powder.

DO NOT USE WATER, moist sand, CO₂, Class ABC, or soda ash extinguisher. Wear protective breathing apparatus; a positive pressure Self Contained Breathing Apparatus (SCBA), or Air Purifying Respirator (APR).

Unusual Fire and Explosion Hazards: Do not short circuit, recharge, over discharge (discharge below 0.0 Volts), puncture, crush or expose to temperatures above 150°C. Cell may leak, vent, or explode. If a bright white flame is present, lithium content is exposed and on fire; use a Class D fire extinguisher, **Do not use water.**

Section 6 – ACCIDENTAL RELEASE MEASURES

Accidental Releases: Do not breathe vapors or touch liquid with bare hands (see section 4). See section 8 for PPE (Personal Protective Equipment) necessary for cleaning or containing an accidental leak.

Waste Disposal Methods: Evacuate area. If possible, a trained person should attempt to stop or contain the leak by neutralizing spill with soda lime or baking soda. A NIOSH Approved Acid Gas Filter Mask or Self-Contained Breathing Apparatus should be worn. Seal leaking battery and soda lime or baking soda in a plastic bag and dispose of as hazardous waste.

Other: Follow North American Emergency Response Guide (NAERG) #138 for cells involved in an accident, cells that have vented, or have exploded.

Section 7 – HANDLING & STORAGE

Storage: Cells should be stored at room temperature, approx. 21°C (70°F). Store cells in the original shipping containers where and when possible.

Precautions: Do not short circuit or expose to temperatures above 150°C. Do not recharge, over discharge, puncture or crush.

Other Conditions: Do not store cells in high humidity environments for long periods of time.

Handling: The cells and batteries are electrical storage devices. To avoid short circuiting the cell and activating the fuse, remove all metallic jewelry, watches, etc from hands or wear gloves. Only handle cells on non-conductive surfaces such as wood, plastic, etc. to avoid shorting the cell. Make sure cells are not exposed to temperatures above 150 °C from heat shrink guns, solder iron, resistance welding, etc. Contact Exium for specific handling and use concerns or questions.

Section 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

When handling internal components:

Respiratory Protection: NIOSH Approved Acid Gas Filter Mask, or Self-Contained Breathing Apparatus.

Protective Gloves: Outer Gloves Nitrile 15 mil (0.015 in), or thicker Inner gloves disposable nitrile. 15 mil PVC provides limited protection. Other glove materials will decompose quickly in contact with thionyl chloride electrolyte and are not recommended.

Eye Protection: Chemical Worker Safety Glasses, lab goggles, or face shield.

Ventilation To Be Used: Negative pressure chemical fume hood.

Other Protective Clothing & Equipment: Protective Apron, Acid Resistant Protective Clothing, and face shield.

Hygienic Work Practices: Use good chemical hygiene practice. Do not eat or drink when handling contents. Avoid unnecessary contact.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

NOT Properties of the Cell

Properties of Internal Components

Thionyl Chloride

Boiling Point:

Vapor Pressure:

Vapor Density:

Solubility in Water:

Specific Gravity:

Melting Point:

Evaporation Rate:

Water Reactive:

Appearance & Odor:

Thionyl Chloride: 77°C

Thionyl Chloride: 92mm @ 20 °C

Thionyl Chloride: 4.1

Thionyl Chloride: Decomposes violently on contact with water to produce HCl and SO₂.

Thionyl Chloride: 1.63

Thionyl Chloride: -105 °C

N/A

Thionyl Chloride hydrolyzes to form SO₂ and HCl gasses and strongly acidic wastewater.

Thionyl Chloride – Colorless to pale yellow; sharp, pungent chlorine type odor.

Lithium

Boiling Point:

Vapor Pressure:

Vapor Density:

Solubility in Water:

Specific Gravity:

Melting Point:

Evaporation Rate:

Water Reactive:

Appearance & Odor:

Lithium Metal: 1336 °C. Auto Ignition in air 179°C (354.2°F)

Lithium Metal: NA at 25 °C

Lithium Metal: NA at 25 °C

Lithium Metal: Decomposes violently on contact with water to produce flammable hydrogen gas. Lithium may also ignite as a result of water contact.

Lithium Metal: 0.543 g / mL

Lithium Metal: 180.5 °C

Lithium Metal NA at 25 °C

Lithium Metal Reacts with water to form hydrogen gas, caustic Lithium Hydroxide, and basic wastewater.

Lithium Metal – Soft silver – white metal. The metal turns yellow, brown, and then black upon exposure to moist air. Lithium metal has no odor.

Section 10 – STABILITY & REACTIVITY

Stability: Stable

Conditions to Avoid: Temperatures in excess of 150 °C. High humidity for extended periods.

Incompatibility: N/A

Hazardous Decomposition Products: Sulfur Dioxide (g), Hydrogen Chloride (g).

Hazardous Polymerization: Will not occur.

Other: N/A

Section 11 – TOXICOLOGICAL INFORMATION

Acute Toxicity:

Thionyl Chloride

LC₅₀ (Inhalation):	1274 ppm (rat 1-hr)
LD₅₀:	N/A
Eye Effects:	Corrosive
Skin Effects:	Corrosive

Gallium (III) Chloride

LD₅₀:	N/A
Eye Effects:	N/A
Other Effects:	N/A

Section 12 – ECOLOGICAL INFORMATION

Aquatic Toxicity: Do not let internal components enter marine environments. Avoid releases into waterways, wastewater or groundwater.

Section 13 – DISPOSAL CONSIDERATIONS

Proper Shipping Name: Waste Lithium Metal Batteries

UN Number: 3090

Hazard Classification: Class 9 (Misc.)

Packing Group: II

Labels Required: MISCELLANEOUS Hazard Class 9, HAZARDOUS WASTE

Waste Disposal Code: D003

Waste Management: Exium Cells may be managed as universal waste, confirm with your local, state, or provincial regulators.

Other: All lithium thionyl chloride batteries should be disposed of by a certified hazardous waste disposal facility. Contact Exium Technologies for recommended disposal facilities.

Section 14 – TRANSPORT INFORMATION

US DOT (per CFR 172.101) and IATA/ICAO

UN Testing Procedure: UN Manual of Test and Criteria Chapter 38.3 Revision 4.0 – This product has been properly tested to ensure product is safe for all means of transport.

Proper Shipping Name Per IATA: Lithium Metal Batteries.

(Note some carriers use the DOT “Lithium Batteries” consult with your carrier if the proper shipping name is in question)

UN Number: UN 3090

Hazard Classification: Class 9 (Misc.) – See IATA 7.4.8 label specifications

Packing Group: II

Packing Instructions: IATA 968, 969, and 970 - To ensure safe transport, it is highly recommended all personnel involved with the packaging, marking, labeling and shipping of this material review these specific packaging procedures to reduce the possibility for an incident to occur while product is in transport. The repercussions of a Lithium Battery incident while in transport could be severe.

Labels Required: MISCELLANEOUS HAZARD CLASS 9 with tab to indicate proper shipping name and UN number.

Other Label Requirements:

- CARGO AIRCRAFT ONLY – This label is required if operator or state regulations specify quantity of material exceeds or is deemed unacceptable for transport via passenger aircraft
- Primary Lithium Batteries – As required by the US DOT, an addition label using the design specifications listed in CFR 49 Part 173.185.b.5 must be applied to each shipping container to identify product as Primary Lithium Batteries.
- Caution Label – As required by IATA regulations, a caution label MUST be applied to each package identifying the enclosed product (Lithium Batteries) and the special procedure to be followed in the event that the package is damaged

Emergency Services: All shipments of hazardous materials MUST include a 24/7 contact number for use in the event of an emergency.

Hazardous Materials Transport Instructional Materials:


- All personnel which will package, label, mark and ship hazardous materials MUST be correctly trained with the below material in order to legally and safely transport hazardous materials.
 1. IATA Dangerous Goods Regulations – Most recent edition available. This document will provide the clearest understanding of handling hazardous materials shipping procedures, and is a MUST if your company will transport hazardous material via AIR.
 2. USDOT CFR 49 Parts 100 – 185 – covers all methods of hazardous material transport with the USA.
 3. Additional research may be required due to specific procedures required by individual operators (carriers) and states (Countries).

Section 15 – REGULATORY INFORMATION

OSHA Status: The internal component (thionyl chloride) is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1920.1200.

Section 16 – OTHER INFORMATION

NFPA RATING



For cells or battery packs involved in an accident, cells that have vented, or exploded, follow the North American Emergency Response Guide (NAERG) #138.

Prepared by: Sean Riley
 Date: 9/17/10
 Updated 1/9/12 Sean Riley